




DB30 DOUBLE BEAM UV-VIS SPECTROPHOTOMETER

The DB30 UV-Vis Spectrophotometer is a high performance double beam instrument suitable for many analytical applications where accurate measurements are key to your results.

The DB30 measures absorption and transmission as a function of wavelength and provides a modern, user-friendly and accurate spectrophotometer for a wide range of sample types and measurements.

Utilising a dual lamp and Czerny-Turner configuration monochromator, the DB30 features a compact, reliable and high throughput optical system which ensures impressive spectral performance. It can be configured with PC control software or as a standalone instrument using the touchscreen included in every DB30 unit.



KEY FEATURES

- > User selectable variable bandpass at 0.5, 1.0, 1.5, 2.0 or 4.0 nm
- > Fast scanning – up to 6,000 nm/min for high sample analysis throughput
- > Automatic accessory recognition
- > Modern touchscreen interface for full standalone control
- > Optional Visacle® software for PC control
- > USB, SD card and internal data storage for convenient retrieval of methods and results



SPECIFICATIONS

DB30 UV-Vis Spectrophotometer

Working Environment and Requirements

Working Temp 10 - 35°C Ambient temperature

Power Supply 100-240 V, 50-60 Hz

Main Specifications

Optics Czerny-Turner, Double Beam Monochromator

Wavelength Range 190 nm – 1100 nm

Spectral Bandwidth 0.5 nm, 1 nm, 1.5 nm, 2 nm and 4 nm

Stray Light ≤0.10% (220 nm NaI, 340 nm NaNO₂)

Wavelength Accuracy ±0.1 nm at D2 peak 656.1 nm

Wavelength Repeatability ±0.1 nm

Photometric Range Absorbance: -3.4 to +3.4, %T: 0 to 300, Concentration: 0.000 to 9,999

Photometric Accuracy ±0.002 Abs (0 - 0.5 Abs), ±0.004 Abs (0.5 - 1.0 Abs), ±0.008 Abs (1.0 - 2.0 Abs), ±0.3% T

Photometric Reproducibility ±0.001 Abs (0 - 0.5 Abs), ±0.002 Abs (0.5 - 1.0 Abs), ±0.004 Abs (1.0 - 2.0 Abs)

Wavelength Scan Speed 10, 100, 200, 400, 800, 1200, 2400, 3600, 6000 nm/min

Noise 0.0001 Abs

Baseline Stability 0.0003 Abs/hr (500 nm, 2 hour lamp warm-up period)

Baseline Flatness ±0.0009 Abs (200 nm - 950 nm)

Light Source Tungsten-Halogen and Deuterium Lamps

Light Source Switching Automatic switching selectable for 325 nm - 370 nm range

Detector Silicon Photodiode

Display 7" Touchscreen

Software Touchscreen operation, PC-controlled software or CFR compliant PC-controlled software

Dimension (L×D×H) 500 mm (W) × 475 mm (D) × 250 mm (H)

Net Weight 20 kg (approx)

Output Device USB flash drive, SD card

Interface USB PC interface

Scope of delivery

Box includes
1 x DB30 Unit
1 x Operation Manual
2 x Quartz Cuvette

After Sales Service

Warranty Guaranteed (under normal maintenance) for one year from the date of delivery

EDINBURGH ANALYTICAL

2 Bain Square, Livingston, EH54 7DQ, United Kingdom

Tel: +44 (0)1506 425 300

Fax: +44 (0)1506 425 320

sales@edinst.com

Registered in England and Wales No: 962331 VAT No:GB 271 7379 37

©Edinburgh Instruments Ltd 2025

STG08 / 06.2025



Customer support is available worldwide

www.edinburghanalytical.com

